

BEST AVAILABLE COPY

I certify that I have transmitted this paper (17 pages) by FAX to the U. S. Patent Trademark Office at 703,872-9306 on Nov. 27, 2004.

By Mario Rabinowitz
Mario Rabinowitz

Minor Specification Correction
To: Mail Stop Issue Fee
Office of Patent Publication/Publishing Division

In The United States Patent And Trademark Office

Serial No. : 10/760,068 Filed: January 16, 2004.
In re Pro Se application of: Mario Rabinowitz
Title: Advanced Micro-Optics Solar Energy Collection System
Examiner: Tuyen Tra; Art. Unit: 2873; ph. 571, 272-2343

RECEIVED
CENTRAL FAX CENTER

MAR 22 2005

Honorable Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

March 21, 2004

Sir:

Applicant is responding to Notice of Drawing Inconsistency
With Specification mailed 3-16-05.

On p. 10 of the specification immediately following the brief description of Fig. 11a, please insert the following brief description:

"Fig. 11b is a block diagram summarizing the training steps of Heating, Vibration, and CW and CCW Rotation."

This was unintentionally left out of the specification.

A full and complete new p. 10 containing this correction is enclosed next. To keep all the original material plus this correction, all on p. 10, some of the original double spacing was changed to 1 1/2 spacing.

Respectfully submitted,

Mario Rabinowitz

Mario Rabinowitz, applicant

Please address correspondence to:

Mario Rabinowitz
715 Lakemead Way
Redwood City, CA 94062

Ph. & FAX 650, 368-4466; e-mail: Mario715@earthlink.net

-2- of 3

BEST AVAILABLE COPY

BEST AVAILABLE COPY

Fig. 7 is a cross-sectional view of a horizontal micro-optics concentrator used in conjunction with a vertical micro-optics concentrator to more efficiently capture the sun's energy and direct it to a receiver.

Fig. 8 is a cross-sectional view of a micro-optics concentrator wherein layers of removable plastic film cover and protect it.

Fig. 9 is a cross-sectional view of a solar receiver, such as a photovoltaic module, showing cooling fins to enhance convective cooling.

Fig. 10a is a top view of a solar receiver showing placement of thermal radiation detectors over its surface.

Fig. 10 b is a schematic of a bridge circuit to detect mis-steering of the concentrated solar beam.

Fig. 11a is a cross-sectional view of apparatus for the training of an ensemble of rotatable mirrored elements in a micro-optics concentrator.

Fig. 11b is a block diagram summarizing the training steps of Heating, Vibration, and CW and CCW Rotation.

**DETAILED DESCRIPTION OF THE
PRESENTLY PREFERRED EMBODIMENTS**

FIG. 1 is a cross-sectional view of an ensemble of rotatable elements 1, each with a micro-mirror surface 2 to reflect the incident sunlight 3 as focussed concentrated light 30 to a receiver 16. The aggregate of the elements 1, together with their containment sheets 11, fluid 70, and addressing system are herein referred to as a micro-optics concentrator 4. The inventor of this instant invention is the co-inventor of U. S. Patent #6,612,705, in which the micro-optics concentrator 4 is described in detail. The combination of the micro-optics concentrator 4 and receiver 16 forms a unique solar collection system. The orientation of the mirrored rotatable elements 1 can be achieved by electric fields, magnetic fields, electromagnetically, electrophoretically, magnetophoretically, etc. Since there is great advantage both from the response to the applied torque, and to the reduction in materials costs by